IP Link® Device Interface
Ethernet Communication Sheet

This document provides additional assistance with wiring your Extron IP Link enabled product to your device. Different components may require a different wiring scheme than those listed below.

For complete operating instructions, refer to the user's manual for the specific Extron IP Link enabled product or the controlled device manufacturer supplied documentation.

Device Specifications:

Device Type:	Camera
Manufacturer:	ACTi
Firmware Version:	N/A
Model(s):	KCM-8111

Minimum Software and Firmware Requirements:

IP Link Compiler	IP Link Firmware	GC Version
1.6.0	1.17	3.5.1

Version History:

Driver Version	Date	Notes
1	10/1/2013	Initial version.

Driver Notes:

- This driver is unidirectional and does not provide any feedback.

Control Commands & States:

Camera Preset Recall	1 to 32	
Flip	Enable	Disable
Mirror	Enable	Disable
Motion Detection	Enable	Disable
Output 1	High	Low
Output 2	High	Low
Power LED	Enable	Disable

Status Available:

N/A

Network communication:

When configuring the Ethernet driver, be sure device settings match that of the GC configuration.

Port Type:	Ethernet
Logon Credentials Supported:	Yes
Default User Name:	admin
Default Port:	80
Multi-Connection Capable:	No
Port Changeable:	Yes

Ethernet Driver Configuration Description:

Please refer to user manual for settings and changes to the network communication parameters such as: User Name, Passwords and Port Number.

Notes for the Device: